


Progress® GFK 尼龙电缆接头

Synthetic cable glands Progress® GFK

公制螺纹 | Entry thread metric



材质: 玻璃纤维增强聚酰胺
性能: 无卤素
密封件: TPE
应力消除: 根据EN62444版本A
温度范围: -20°C / +100°C
防护等级: IP68

Material: Polyamide glass fiber reinforced
Properties: halogen-free
Seal: TPE
Strain relief: Version A acc. to EN 62444
Temperature range: -20°C / +100°C
Protection class: IP 68



Progress GFK

浅灰色RAL7035
单体密封件

Light grey RAL 7035
One-piece sealing insert

| G | >Ø< min mm | >Ø< max mm | Ø mm | H mm | L mm | 型号 Art. No. | |
|---------|---------------|---------------|---------|---------|---------|---------------|----|
| M8x1.0 | 2.5 | 3.5 | 12 | 15.5 | 10 | 1571.08.035 | 50 |
| M8x1.0 | 3.5 | 5.0 | 12 | 15.5 | 10 | 1571.08.050 | 50 |
| M10x1.0 | 3.0 | 4.0 | 15 | 18.0 | 10 | 1571.10.040 | 50 |
| M10x1.0 | 4.0 | 6.0 | 15 | 18.0 | 10 | 1571.10.060 | 50 |
| M12x1.5 | 3.5 | 5.0 | 17 | 22.0 | 12 | 1571.12.050 | 50 |
| M12x1.5 | 5.0 | 6.5 | 17 | 22.0 | 12 | 1571.12.065 | 50 |
| M12x1.5 | 6.5 | 8.0 | 17 | 22.0 | 12 | 1571.12.080 | 50 |
| M16x1.5 | 4.5 | 6.0 | 21 | 26.0 | 12 | 1571.17.060 | 50 |
| M16x1.5 | 6.0 | 8.0 | 21 | 26.0 | 12 | 1571.17.080 | 50 |
| M16x1.5 | 8.0 | 10.5 | 21 | 26.0 | 12 | 1571.17.105 | 50 |
| M20x1.5 | 6.0 | 8.0 | 27 | 28.0 | 13 | 1571.20.080 | 50 |
| M20x1.5 | 8.0 | 11.0 | 27 | 28.0 | 13 | 1571.20.110 | 50 |
| M20x1.5 | 11.0 | 15.0 | 27 | 28.0 | 13 | 1571.20.150 | 50 |
| M25x1.5 | 9.5 | 12.5 | 34 | 33.0 | 13 | 1571.25.125 | 25 |
| M25x1.5 | 12.5 | 16.0 | 34 | 33.0 | 13 | 1571.25.160 | 25 |
| M25x1.5 | 16.0 | 20.5 | 34 | 33.0 | 13 | 1571.25.205 | 25 |
| M32x1.5 | 14.0 | 17.0 | 41 | 35.0 | 15 | 1571.32.170 | 25 |
| M32x1.5 | 17.0 | 21.0 | 41 | 35.0 | 15 | 1571.32.210 | 25 |
| M32x1.5 | 21.0 | 25.5 | 41 | 35.0 | 15 | 1571.32.255 | 25 |
| M40x1.5 | 20.0 | 24.0 | 50 | 40.0 | 15 | 1571.40.240 | 10 |
| M40x1.5 | 24.0 | 28.5 | 50 | 40.0 | 15 | 1571.40.285 | 10 |
| M40x1.5 | 28.5 | 33.0 | 50 | 40.0 | 15 | 1571.40.330 | 10 |
| M50x1.5 | 29.0 | 33.0 | 60 | 42.0 | 16 | 1571.50.330 | 10 |
| M50x1.5 | 33.0 | 37.0 | 60 | 42.0 | 16 | 1571.50.370 | 10 |
| M50x1.5 | 37.0 | 42.0 | 60 | 42.0 | 16 | 1571.50.420 | 10 |
| M63x1.5 | 35.0 | 40.0 | 75 | 48.0 | 16 | 1571.63.400 | 5 |
| M63x1.5 | 40.0 | 46.0 | 75 | 48.0 | 16 | 1571.63.460 | 5 |
| M63x1.5 | 46.0 | 52.0 | 75 | 48.0 | 16 | 1571.63.520 | 5 |



Progress GFK

浅灰色RAL7035
两件套密封件

Light grey RAL 7035
Two-piece sealing insert

| G | >Ø< min mm | >Ø< max mm | >Ø< min mm | >Ø< max mm | Ø mm | H mm | L mm | 型号 Art. No. | |
|---------|---------------|---------------|---------------|---------------|---------|---------|---------|---------------|----|
| M16x1.5 | 6.0 | 8.0 | 8.0 | 10.5 | 21 | 26.0 | 12 | 1571.17 | 50 |
| M20x1.5 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28.0 | 13 | 1571.20 | 50 |
| M25x1.5 | 12.5 | 16.0 | 16.0 | 20.5 | 34 | 33.0 | 13 | 1571.25 | 25 |
| M32x1.5 | 17.0 | 21.0 | 21.0 | 25.5 | 41 | 35.0 | 15 | 1571.32 | 25 |
| M40x1.5 | 24.0 | 28.5 | 28.5 | 33.0 | 50 | 40.0 | 15 | 1571.40 | 10 |
| M50x1.5 | 33.0 | 37.0 | 37.0 | 42.0 | 60 | 42.0 | 16 | 1571.50 | 10 |
| M63x1.5 | 40.0 | 46.0 | 46.0 | 52.0 | 75 | 48.0 | 16 | 1571.63 | 5 |

材质: 玻璃纤维增强AGROMID
抗热老化和高耐冲性

性能: 无卤素

密封件: TPE

应力消除: 根据EN62444版本A

温度范围: -30°C / +100°C

防护等级: IP68

Material: Agromid glass fiber reinforced, heat aging and impact-resistant modified


Properties: halogen-free

Seal: TPE

Strain relief: Version A acc. to EN 62444

Temperature range: -30°C / +100°C

Protection class: IP 68



Progress GFK

| 深灰色RAL7001 单体密封件 | | Dark grey RAL 7001 One-piece sealing insert | | | | | | 型号 Art. No. | 📦 |
|---------------------|---------------|--|---------|---------|---------|--|-------------|---------------|---|
| G | >Ø< min mm | >Ø< max mm | Ø mm | H mm | L mm | | | | |
| M8x1.0 | 2.5 | 3.5 | 12 | 15.5 | 10 | | 1572.08.035 | 50 | |
| M8x1.0 | 3.5 | 5.0 | 12 | 15.5 | 10 | | 1572.08.050 | 50 | |
| M10x1.0 | 3.0 | 4.0 | 15 | 18.0 | 10 | | 1572.10.040 | 50 | |
| M10x1.0 | 4.0 | 6.0 | 15 | 18.0 | 10 | | 1572.10.060 | 50 | |
| M12x1.5 | 3.5 | 5.0 | 17 | 22.0 | 12 | | 1572.12.050 | 50 | |
| M12x1.5 | 5.0 | 6.5 | 17 | 22.0 | 12 | | 1572.12.065 | 50 | |
| M12x1.5 | 6.5 | 8.0 | 17 | 22.0 | 12 | | 1572.12.080 | 50 | |
| M16x1.5 | 4.5 | 6.0 | 21 | 26.0 | 12 | | 1572.17.060 | 50 | |
| M16x1.5 | 6.0 | 8.0 | 21 | 26.0 | 12 | | 1572.17.080 | 50 | |
| M16x1.5 | 8.0 | 10.5 | 21 | 26.0 | 12 | | 1572.17.105 | 50 | |
| M20x1.5 | 6.0 | 8.0 | 27 | 28.0 | 13 | | 1572.20.080 | 50 | |
| M20x1.5 | 8.0 | 11.0 | 27 | 28.0 | 13 | | 1572.20.110 | 50 | |
| M20x1.5 | 11.0 | 15.0 | 27 | 28.0 | 13 | | 1572.20.150 | 50 | |
| M25x1.5 | 9.5 | 12.5 | 34 | 33.0 | 13 | | 1572.25.125 | 25 | |
| M25x1.5 | 12.5 | 16.0 | 34 | 33.0 | 13 | | 1572.25.160 | 25 | |
| M25x1.5 | 16.0 | 20.5 | 34 | 33.0 | 13 | | 1572.25.205 | 25 | |
| M32x1.5 | 14.0 | 17.0 | 41 | 35.0 | 15 | | 1572.32.170 | 25 | |
| M32x1.5 | 17.0 | 21.0 | 41 | 35.0 | 15 | | 1572.32.210 | 25 | |
| M32x1.5 | 21.0 | 25.5 | 41 | 35.0 | 15 | | 1572.32.255 | 25 | |
| M40x1.5 | 20.0 | 24.0 | 50 | 40.0 | 15 | | 1572.40.240 | 10 | |
| M40x1.5 | 24.0 | 28.5 | 50 | 40.0 | 15 | | 1572.40.285 | 10 | |
| M40x1.5 | 28.5 | 33.0 | 50 | 40.0 | 15 | | 1572.40.330 | 10 | |
| M50x1.5 | 29.0 | 33.0 | 60 | 42.0 | 16 | | 1572.50.330 | 10 | |
| M50x1.5 | 33.0 | 37.0 | 60 | 42.0 | 16 | | 1572.50.370 | 10 | |
| M50x1.5 | 37.0 | 42.0 | 60 | 42.0 | 16 | | 1572.50.420 | 10 | |
| M63x1.5 | 35.0 | 40.0 | 75 | 48.0 | 16 | | 1572.63.400 | 5 | |
| M63x1.5 | 40.0 | 46.0 | 75 | 48.0 | 16 | | 1572.63.460 | 5 | |
| M63x1.5 | 46.0 | 52.0 | 75 | 48.0 | 16 | | 1572.63.520 | 5 | |



Progress GFK


| 深灰色RAL7001 两件套密封件 | | Dark grey RAL 7001 Two-piece sealing insert | | | | | | 型号 Art. No. | 📦 |
|----------------------|---------------|--|---------------|---------------|---------|---------|---------|---------------|----|
| G | >Ø< min mm | >Ø< max mm | >Ø< min mm | >Ø< max mm | Ø mm | H mm | L mm | | |
| M16x1.5 | 6.0 | 8.0 | 8.0 | 10.5 | 21 | 26.0 | 12 | 1572.17 | 50 |
| M20x1.5 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28.0 | 13 | 1572.20 | 50 |
| M25x1.5 | 12.5 | 16.0 | 16.0 | 20.5 | 34 | 33.0 | 13 | 1572.25 | 25 |
| M32x1.5 | 17.0 | 21.0 | 21.0 | 25.5 | 41 | 35.0 | 15 | 1572.32 | 25 |
| M40x1.5 | 24.0 | 28.5 | 28.5 | 33.0 | 50 | 40.0 | 15 | 1572.40 | 10 |
| M50x1.5 | 33.0 | 37.0 | 37.0 | 42.0 | 60 | 42.0 | 16 | 1572.50 | 10 |
| M63x1.5 | 40.0 | 46.0 | 46.0 | 52.0 | 75 | 48.0 | 16 | 1572.63 | 5 |



Progress® GFK 尼龙电缆接头

Synthetic cable glands Progress® GFK

公制螺纹 | Entry thread metric



材质: 玻璃纤维增强聚酰胺
性能: 无卤素
密封件: TPE
应力消除: 根据EN62444版本A
温度范围: -20°C / +100°C
防护等级: IP68

Material: Polyamide glass fiber reinforced
Properties: halogen-free
Seal: TPE
Strain relief: Version A acc. to EN 62444
Temperature range: -20°C / +100°C
Protection class: IP 68



Progress GFK

黑色RAL9005
单体密封件

Black RAL 9005
One-piece sealing insert

| G | $\begin{matrix} > \text{Ø} < \\ \text{min mm} \end{matrix}$ | $\begin{matrix} > \text{Ø} < \\ \text{max mm} \end{matrix}$ | $\begin{matrix} \text{Ø} \\ \text{mm} \end{matrix}$ | H mm | L mm | 型号 Art. No. | |
|---------|---|---|---|---------|---------|---------------|----|
| M8x1.0 | 2.5 | 3.5 | 12 | 15.5 | 10 | 1540.08.035 | 50 |
| M8x1.0 | 3.5 | 5.0 | 12 | 15.5 | 10 | 1540.08.050 | 50 |
| M10x1.0 | 3.0 | 4.0 | 15 | 18.0 | 10 | 1540.10.040 | 50 |
| M10x1.0 | 4.0 | 6.0 | 15 | 18.0 | 10 | 1540.10.060 | 50 |
| M12x1.5 | 3.5 | 5.0 | 17 | 22.0 | 12 | 1540.12.050 | 50 |
| M12x1.5 | 5.0 | 6.5 | 17 | 22.0 | 12 | 1540.12.065 | 50 |
| M12x1.5 | 6.5 | 8.0 | 17 | 22.0 | 12 | 1540.12.080 | 50 |
| M16x1.5 | 4.5 | 6.0 | 21 | 26.0 | 12 | 1540.17.060 | 50 |
| M16x1.5 | 6.0 | 8.0 | 21 | 26.0 | 12 | 1540.17.080 | 50 |
| M16x1.5 | 8.0 | 10.5 | 21 | 26.0 | 12 | 1540.17.105 | 50 |
| M20x1.5 | 6.0 | 8.0 | 27 | 28.0 | 13 | 1540.20.080 | 50 |
| M20x1.5 | 8.0 | 11.0 | 27 | 28.0 | 13 | 1540.20.110 | 50 |
| M20x1.5 | 11.0 | 15.0 | 27 | 28.0 | 13 | 1540.20.150 | 50 |
| M25x1.5 | 9.5 | 12.5 | 34 | 33.0 | 13 | 1540.25.125 | 25 |
| M25x1.5 | 12.5 | 16.0 | 34 | 33.0 | 13 | 1540.25.160 | 25 |
| M25x1.5 | 16.0 | 20.5 | 34 | 33.0 | 13 | 1540.25.205 | 25 |
| M32x1.5 | 14.0 | 17.0 | 41 | 35.0 | 15 | 1540.32.170 | 25 |
| M32x1.5 | 17.0 | 21.0 | 41 | 35.0 | 15 | 1540.32.210 | 25 |
| M32x1.5 | 21.0 | 25.5 | 41 | 35.0 | 15 | 1540.32.255 | 25 |
| M40x1.5 | 20.0 | 24.0 | 50 | 40.0 | 15 | 1540.40.240 | 10 |
| M40x1.5 | 24.0 | 28.5 | 50 | 40.0 | 15 | 1540.40.285 | 10 |
| M40x1.5 | 28.5 | 33.0 | 50 | 40.0 | 15 | 1540.40.330 | 10 |
| M50x1.5 | 29.0 | 33.0 | 60 | 42.0 | 16 | 1540.50.330 | 10 |
| M50x1.5 | 33.0 | 37.0 | 60 | 42.0 | 16 | 1540.50.370 | 10 |
| M50x1.5 | 37.0 | 42.0 | 60 | 42.0 | 16 | 1540.50.420 | 10 |
| M63x1.5 | 35.0 | 40.0 | 75 | 48.0 | 16 | 1540.63.400 | 5 |
| M63x1.5 | 40.0 | 46.0 | 75 | 48.0 | 16 | 1540.63.460 | 5 |
| M63x1.5 | 46.0 | 52.0 | 75 | 48.0 | 16 | 1540.63.520 | 5 |



Progress GFK


黑色RAL9005
两件套密封件

Black RAL 9005
Two-piece sealing insert

| G | $\begin{matrix} > \text{Ø} < \\ \text{min mm} \end{matrix}$ | $\begin{matrix} > \text{Ø} < \\ \text{max mm} \end{matrix}$ | $\begin{matrix} > \text{Ø} < \\ \text{min mm} \end{matrix}$ | $\begin{matrix} > \text{Ø} < \\ \text{max mm} \end{matrix}$ | $\begin{matrix} \text{Ø} \\ \text{mm} \end{matrix}$ | H mm | L mm | 型号 Art. No. | |
|---------|---|---|---|---|---|---------|---------|---------------|----|
| M16x1.5 | 6.0 | 8.0 | 8.0 | 10.5 | 21 | 26.0 | 12 | 1540.17 | 50 |
| M20x1.5 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28.0 | 13 | 1540.20 | 50 |
| M25x1.5 | 12.5 | 16.0 | 16.0 | 20.5 | 34 | 33.0 | 13 | 1540.25 | 25 |
| M32x1.5 | 17.0 | 21.0 | 21.0 | 25.5 | 41 | 35.0 | 15 | 1540.32 | 25 |
| M40x1.5 | 24.0 | 28.5 | 28.5 | 33.0 | 50 | 40.0 | 15 | 1540.40 | 10 |
| M50x1.5 | 33.0 | 37.0 | 37.0 | 42.0 | 60 | 42.0 | 16 | 1540.50 | 10 |
| M63x1.5 | 40.0 | 46.0 | 46.0 | 52.0 | 75 | 48.0 | 16 | 1540.63 | 5 |

材质: 玻璃纤维增强聚酰胺
 性能: 无卤素
 密封件: TPE
 应力消除: 根据EN62444版本A
 温度范围: -20°C / +100°C
 防护等级: IP68

Material: Polyamide glass fiber reinforced
 Properties: halogen-free
 Seal: TPE
 Strain relief: Version A acc. to EN 62444
 Temperature range: -20°C / +100°C
 Protection class: IP 68



Progress GFK

| 白色RAL9010 单体密封件 | | White RAL 9010 One-piece sealing insert | | 型号 Art. No. | | 📦 |
|--------------------|-----------------|--|----|---------------|---------|----------------|
| G | > Ø < min mm | > Ø < max mm | mm | H mm | L mm | |
| M20x1.5 | 6.0 | 8.0 | 27 | 28 | 13 | 1520.20.080 50 |
| M20x1.5 | 8.0 | 11.0 | 27 | 28 | 13 | 1520.20.110 50 |



Progress GFK

| 白色RAL9010 两件套密封件 | | White RAL 9010 Two-piece sealing insert | | 型号 Art. No. | | 📦 | | |
|---------------------|-----------------|--|-----------------|-----------------|----|---------|---------|------------|
| G | > Ø < min mm | > Ø < max mm | > Ø < min mm | > Ø < max mm | mm | H mm | L mm | |
| M16x1.5 | 6.0 | 8.0 | 8.0 | 10.5 | 21 | 26 | 12 | 1520.17 50 |
| M20x1.5 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1520.20 50 |
| M25x1.5 | 12.5 | 16.0 | 16.0 | 20.5 | 34 | 33 | 13 | 1520.25 25 |



Progress GFK


| 灰绿色RAL7009 两件套密封件 | | Greygreen RAL 7009 Two-piece sealing insert | | 型号 Art. No. | | 📦 | | |
|----------------------|-----------------|--|-----------------|-----------------|----|---------|---------|------------|
| G | > Ø < min mm | > Ø < max mm | > Ø < min mm | > Ø < max mm | mm | H mm | L mm | |
| M16x1.5 | 6.0 | 8.0 | 8.0 | 10.5 | 21 | 26 | 12 | 1570.17 50 |
| M20x1.5 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1570.20 50 |
| M25x1.5 | 12.5 | 16.0 | 16.0 | 20.5 | 34 | 33 | 13 | 1570.25 25 |
| M32x1.5 | 17.0 | 21.0 | 21.0 | 25.5 | 41 | 35 | 15 | 1570.32 25 |



Progress® GFK 尼龙电缆接头

Synthetic cable glands Progress® GFK

Pg 螺纹 | Entry thread Pg



材质: 玻璃纤维增强聚酰胺
性能: 无卤素
密封件: TPE
温度范围: -20°C / +100°C
防护等级: IP68

Material: Polyamide glass fiber reinforced
Properties: halogen-free
Seal: TPE
Temperature range: -20°C / +100°C
Protection class: IP 68



Progress GFK

浅灰色RAL7035
单体密封件

Light grey RAL 7035
One-piece sealing insert

| G | >Ø< min mm | >Ø< max mm | Ø mm | H mm | L mm | 型号 Art. No. | |
|-------|---------------|---------------|---------|---------|---------|---------------|----|
| Pg 7 | 3.5 | 5.0 | 17 | 22 | 12 | 1571.07.050 | 50 |
| Pg 7 | 5.0 | 6.5 | 17 | 22 | 12 | 1571.07.065 | 50 |
| Pg 7 | 6.5 | 8.0 | 17 | 22 | 12 | 1571.07.080 | 50 |
| Pg 9 | 4.5 | 6.0 | 21 | 26 | 12 | 1571.09.060 | 50 |
| Pg 9 | 6.0 | 8.0 | 21 | 26 | 12 | 1571.09.080 | 50 |
| Pg 9 | 8.0 | 10.5 | 21 | 26 | 12 | 1571.09.105 | 50 |
| Pg 11 | 4.0 | 5.5 | 24 | 28 | 12 | 1571.11.055 | 50 |
| Pg 11 | 5.5 | 8.5 | 24 | 28 | 12 | 1571.11.085 | 50 |
| Pg 11 | 8.5 | 12.0 | 24 | 28 | 12 | 1571.11.120 | 50 |
| Pg 13 | 6.0 | 8.0 | 27 | 28 | 13 | 1571.13.080 | 50 |
| Pg 13 | 8.0 | 11.0 | 27 | 28 | 13 | 1571.13.110 | 50 |
| Pg 13 | 11.0 | 15.0 | 27 | 28 | 13 | 1571.13.150 | 50 |
| Pg 16 | 6.0 | 8.0 | 27 | 28 | 13 | 1571.16.080 | 50 |
| Pg 16 | 8.0 | 11.0 | 27 | 28 | 13 | 1571.16.110 | 50 |
| Pg 16 | 11.0 | 15.0 | 27 | 28 | 13 | 1571.16.150 | 50 |
| Pg 21 | 9.5 | 12.5 | 34 | 33 | 13 | 1571.21.125 | 25 |
| Pg 21 | 12.5 | 16.0 | 34 | 33 | 13 | 1571.21.160 | 25 |
| Pg 21 | 16.0 | 20.5 | 34 | 33 | 13 | 1571.21.205 | 25 |
| Pg 29 | 16.0 | 19.0 | 41 | 36 | 13 | 1571.29.190 | 25 |
| Pg 29 | 19.0 | 23.0 | 41 | 36 | 13 | 1571.29.230 | 25 |
| Pg 29 | 23.0 | 27.5 | 41 | 36 | 13 | 1571.29.275 | 25 |
| Pg 36 | 21.5 | 26.0 | 55 | 42 | 16 | 1571.36.260 | 10 |
| Pg 36 | 26.0 | 30.5 | 55 | 42 | 16 | 1571.36.305 | 10 |
| Pg 36 | 30.5 | 35.0 | 55 | 42 | 16 | 1571.36.350 | 10 |
| Pg 42 | 29.0 | 33.0 | 60 | 42 | 16 | 1571.42.330 | 10 |
| Pg 42 | 33.0 | 37.0 | 60 | 42 | 16 | 1571.42.370 | 10 |
| Pg 42 | 37.0 | 42.0 | 60 | 42 | 16 | 1571.42.420 | 10 |
| Pg 48 | 32.0 | 37.0 | 70 | 46 | 16 | 1571.48.370 | 5 |
| Pg 48 | 37.0 | 43.0 | 70 | 46 | 16 | 1571.48.430 | 5 |
| Pg 48 | 43.0 | 49.0 | 70 | 46 | 16 | 1571.48.490 | 5 |



Progress GFK

浅灰色RAL7035
两件套密封件

Light grey RAL 7035
Two-piece sealing insert

| G | >Ø< min mm | >Ø< max mm | >Ø< min mm | >Ø< max mm | Ø mm | H mm | L mm | 型号 Art. No. | |
|-------|---------------|---------------|---------------|---------------|---------|---------|---------|---------------|----|
| Pg 9 | 6.0 | 8.0 | 8.0 | 10.5 | 21 | 26 | 12 | 1571.09 | 50 |
| Pg 11 | 5.5 | 8.5 | 8.5 | 12.0 | 24 | 28 | 12 | 1571.11 | 50 |
| Pg 13 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1571.13 | 50 |
| Pg 16 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1571.16 | 50 |
| Pg 21 | 12.5 | 16.0 | 16.0 | 20.5 | 34 | 33 | 13 | 1571.21 | 25 |
| Pg 29 | 19.0 | 23.0 | 23.0 | 27.5 | 41 | 36 | 13 | 1571.29 | 25 |
| Pg 36 | 26.0 | 30.5 | 30.5 | 35.0 | 55 | 42 | 16 | 1571.36 | 10 |
| Pg 42 | 33.0 | 37.0 | 37.0 | 42.0 | 60 | 42 | 16 | 1571.42 | 10 |
| Pg 48 | 37.0 | 43.0 | 43.0 | 49.0 | 70 | 46 | 16 | 1571.48 | 5 |

材质: 玻璃纤维增强 AGROMID
抗热老化和高耐冲性

Material: Agromid glass fiber reinforced, heat aging and impact-resistant modified

性能: 无卤素

Properties: halogen-free

密封件: TPE


Seal: TPE

温度范围: -30°C / +100°C

Temperature range: -30°C / +100°C

防护等级: IP68

Protection class: IP 68



Progress GFK



深灰色RAL7001
单体密封件

Dark grey RAL 7001
One-piece sealing insert

| G | >Ø< min mm | >Ø< max mm | mm | H mm | L mm | 型号 Art. No. | 📦 |
|-------|---------------|---------------|----|---------|---------|---------------|----|
| Pg 7 | 3.5 | 5.0 | 17 | 22 | 12 | 1572.07.050 | 50 |
| Pg 7 | 5.0 | 6.5 | 17 | 22 | 12 | 1572.07.065 | 50 |
| Pg 7 | 6.5 | 8.0 | 17 | 22 | 12 | 1572.07.080 | 50 |
| Pg 9 | 4.5 | 6.0 | 21 | 26 | 12 | 1572.09.060 | 50 |
| Pg 9 | 6.0 | 8.0 | 21 | 26 | 12 | 1572.09.080 | 50 |
| Pg 9 | 8.0 | 10.5 | 21 | 26 | 12 | 1572.09.105 | 50 |
| Pg 11 | 4.0 | 5.5 | 24 | 28 | 12 | 1572.11.055 | 50 |
| Pg 11 | 5.5 | 8.5 | 24 | 28 | 12 | 1572.11.085 | 50 |
| Pg 11 | 8.5 | 12.0 | 24 | 28 | 12 | 1572.11.120 | 50 |
| Pg 13 | 6.0 | 8.0 | 27 | 28 | 13 | 1572.13.080 | 50 |
| Pg 13 | 8.0 | 11.0 | 27 | 28 | 13 | 1572.13.110 | 50 |
| Pg 13 | 11.0 | 15.0 | 27 | 28 | 13 | 1572.13.150 | 50 |
| Pg 16 | 6.0 | 8.0 | 27 | 28 | 13 | 1572.16.080 | 50 |
| Pg 16 | 8.0 | 11.0 | 27 | 28 | 13 | 1572.16.110 | 50 |
| Pg 16 | 11.0 | 15.0 | 27 | 28 | 13 | 1572.16.150 | 50 |
| Pg 21 | 9.5 | 12.5 | 34 | 33 | 13 | 1572.21.125 | 25 |
| Pg 21 | 12.5 | 16.0 | 34 | 33 | 13 | 1572.21.160 | 25 |
| Pg 21 | 16.0 | 20.5 | 34 | 33 | 13 | 1572.21.205 | 25 |
| Pg 29 | 16.0 | 19.0 | 41 | 36 | 13 | 1572.29.190 | 25 |
| Pg 29 | 19.0 | 23.0 | 41 | 36 | 13 | 1572.29.230 | 25 |
| Pg 29 | 23.0 | 27.5 | 41 | 36 | 13 | 1572.29.275 | 25 |
| Pg 36 | 21.5 | 26.0 | 55 | 42 | 16 | 1572.36.260 | 10 |
| Pg 36 | 26.0 | 30.5 | 55 | 42 | 16 | 1572.36.305 | 10 |
| Pg 36 | 30.5 | 35.0 | 55 | 42 | 16 | 1572.36.350 | 10 |
| Pg 42 | 29.0 | 33.0 | 60 | 42 | 16 | 1572.42.330 | 10 |
| Pg 42 | 33.0 | 37.0 | 60 | 42 | 16 | 1572.42.370 | 10 |
| Pg 42 | 37.0 | 42.0 | 60 | 42 | 16 | 1572.42.420 | 10 |
| Pg 48 | 32.0 | 37.0 | 70 | 46 | 16 | 1572.48.370 | 5 |
| Pg 48 | 37.0 | 43.0 | 70 | 46 | 16 | 1572.48.430 | 5 |
| Pg 48 | 43.0 | 49.0 | 70 | 46 | 16 | 1572.48.490 | 5 |



Progress GFK



深灰色RAL7001
两件套密封件

Dark grey RAL 7001
Two-piece sealing insert


| G | >Ø< min mm | >Ø< max mm | >Ø< min mm | >Ø< max mm | mm | H mm | L mm | 型号 Art. No. | 📦 |
|-------|---------------|---------------|---------------|---------------|----|---------|---------|---------------|----|
| Pg 9 | 6.0 | 8.0 | 8.0 | 10.5 | 21 | 26 | 12 | 1572.09 | 50 |
| Pg 11 | 5.5 | 8.5 | 8.5 | 12.0 | 24 | 28 | 12 | 1572.11 | 50 |
| Pg 13 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1572.13 | 50 |
| Pg 16 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1572.16 | 50 |
| Pg 21 | 12.5 | 16.0 | 16.0 | 20.5 | 34 | 33 | 13 | 1572.21 | 25 |
| Pg 29 | 19.0 | 23.0 | 23.0 | 27.5 | 41 | 36 | 13 | 1572.29 | 25 |
| Pg 36 | 26.0 | 30.5 | 30.5 | 35.0 | 55 | 42 | 16 | 1572.36 | 10 |
| Pg 42 | 33.0 | 37.0 | 37.0 | 42.0 | 60 | 42 | 16 | 1572.42 | 10 |
| Pg 48 | 37.0 | 43.0 | 43.0 | 49.0 | 70 | 46 | 16 | 1572.48 | 5 |



Progress® GFK 尼龙电缆接头

Synthetic cable glands Progress® GFK

Pg 螺纹 | Entry thread Pg



材质: 玻璃纤维增强聚酰胺
性能: 无卤素
密封件: TPE
温度范围: -20°C / +100°C
防护等级: IP68

Material: Polyamide glass fiber reinforced
Properties: halogen-free
Seal: TPE
Temperature range: -20°C / +100°C
Protection class: IP 68



Progress GFK

黑色RAL9005
单体密封件

Black RAL 9005
One-piece sealing insert

| G | >Ø< min mm | >Ø< max mm | Ø mm | H mm | L mm | 型号 Art. No. | ☐ |
|-------|---------------|---------------|---------|---------|---------|---------------|----|
| Pg 7 | 3.5 | 5.0 | 17 | 22 | 12 | 1540.07.050 | 50 |
| Pg 7 | 5.0 | 6.5 | 17 | 22 | 12 | 1540.07.065 | 50 |
| Pg 7 | 6.5 | 8.0 | 17 | 22 | 12 | 1540.07.080 | 50 |
| Pg 9 | 4.5 | 6.0 | 21 | 26 | 12 | 1540.09.060 | 50 |
| Pg 9 | 6.0 | 8.0 | 21 | 26 | 12 | 1540.09.080 | 50 |
| Pg 9 | 8.0 | 10.5 | 21 | 26 | 12 | 1540.09.105 | 50 |
| Pg 11 | 4.0 | 5.5 | 24 | 28 | 12 | 1540.11.055 | 50 |
| Pg 11 | 5.5 | 8.5 | 24 | 28 | 12 | 1540.11.085 | 50 |
| Pg 11 | 8.5 | 12.0 | 24 | 28 | 12 | 1540.11.120 | 50 |
| Pg 13 | 6.0 | 8.0 | 27 | 28 | 13 | 1540.13.080 | 50 |
| Pg 13 | 8.0 | 11.0 | 27 | 28 | 13 | 1540.13.110 | 50 |
| Pg 13 | 11.0 | 15.0 | 27 | 28 | 13 | 1540.13.150 | 50 |
| Pg 16 | 6.0 | 8.0 | 27 | 28 | 13 | 1540.16.080 | 50 |
| Pg 16 | 8.0 | 11.0 | 27 | 28 | 13 | 1540.16.110 | 50 |
| Pg 16 | 11.0 | 15.0 | 27 | 28 | 13 | 1540.16.150 | 50 |
| Pg 21 | 9.5 | 12.5 | 34 | 33 | 13 | 1540.21.125 | 25 |
| Pg 21 | 12.5 | 16.0 | 34 | 33 | 13 | 1540.21.160 | 25 |
| Pg 21 | 16.0 | 20.5 | 34 | 33 | 13 | 1540.21.205 | 25 |
| Pg 29 | 16.0 | 19.0 | 41 | 36 | 13 | 1540.29.190 | 25 |
| Pg 29 | 19.0 | 23.0 | 41 | 36 | 13 | 1540.29.230 | 25 |
| Pg 29 | 23.0 | 27.5 | 41 | 36 | 13 | 1540.29.275 | 25 |
| Pg 36 | 21.5 | 26.0 | 55 | 42 | 16 | 1540.36.260 | 10 |
| Pg 36 | 26.0 | 30.5 | 55 | 42 | 16 | 1540.36.305 | 10 |
| Pg 36 | 30.5 | 35.0 | 55 | 42 | 16 | 1540.36.350 | 10 |
| Pg 42 | 29.0 | 33.0 | 60 | 42 | 16 | 1540.42.330 | 10 |
| Pg 42 | 33.0 | 37.0 | 60 | 42 | 16 | 1540.42.370 | 10 |
| Pg 42 | 37.0 | 42.0 | 60 | 42 | 16 | 1540.42.420 | 10 |
| Pg 48 | 32.0 | 37.0 | 70 | 46 | 16 | 1540.48.370 | 5 |
| Pg 48 | 37.0 | 43.0 | 70 | 46 | 16 | 1540.48.430 | 5 |
| Pg 48 | 43.0 | 49.0 | 70 | 46 | 16 | 1540.48.490 | 5 |




Progress GFK

黑色RAL9005
两件套密封件

Black RAL 9005
Two-piece sealing insert

| G | >Ø< min mm | >Ø< max mm | >Ø< min mm | >Ø< max mm | Ø mm | H mm | L mm | 型号 Art. No. | ☐ |
|-------|---------------|---------------|---------------|---------------|---------|---------|---------|---------------|----|
| Pg 9 | 6.0 | 8.0 | 8.0 | 10.5 | 21 | 26 | 12 | 1540.09 | 50 |
| Pg 11 | 5.5 | 8.5 | 8.5 | 12.0 | 24 | 28 | 12 | 1540.11 | 50 |
| Pg 13 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1540.13 | 50 |
| Pg 16 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1540.16 | 50 |
| Pg 21 | 12.5 | 16.0 | 16.0 | 20.5 | 34 | 33 | 13 | 1540.21 | 25 |
| Pg 29 | 19.0 | 23.0 | 23.0 | 27.5 | 41 | 36 | 13 | 1540.29 | 25 |
| Pg 36 | 26.0 | 30.5 | 30.5 | 35.0 | 55 | 42 | 16 | 1540.36 | 10 |
| Pg 42 | 33.0 | 37.0 | 37.0 | 42.0 | 60 | 42 | 16 | 1540.42 | 10 |
| Pg 48 | 37.0 | 43.0 | 43.0 | 49.0 | 70 | 46 | 16 | 1540.48 | 5 |

| | | | |
|-------|----------------|--------------------|----------------------------------|
| 材质: | 玻璃纤维增强聚酰胺 | Material: | Polyamide glass fiber reinforced |
| 性能: | 无卤素 | Properties: | halogen-free |
| 密封件: | TPE | Seal: | TPE |
| 温度范围: | -20°C / +100°C | Temperature range: | -20°C / +100°C |
| 防护等级: | IP68 | Protection class: | IP 68 |



Progress GFK

| 白色RAL9010 单体密封件 | | | | | | | White RAL 9010 One-piece sealing insert | | | |
|--------------------|-----------------|-----------------|----|---------|---------|--------------------|--|--|--|--|
| G | > Ø < min mm | > Ø < max mm | mm | H mm | L mm | 型号 Art. No. | 📦 | | | |
| Pg 16 | 6.0 | 8.0 | 27 | 28 | 13 | 1520.16.080 | 50 | | | |
| Pg 16 | 8.0 | 11.0 | 27 | 28 | 13 | 1520.16.110 | 50 | | | |



Progress GFK

| 白色RAL9010 两件套密封件 | | | | | | | White RAL 9010 Two-piece sealing insert | | | |
|---------------------|-----------------|-----------------|-----------------|-----------------|----|---------|--|----------------|----|--|
| G | > Ø < min mm | > Ø < max mm | > Ø < min mm | > Ø < max mm | mm | H mm | L mm | 型号 Art. No. | 📦 | |
| Pg 11 | 5.5 | 8.5 | 8.5 | 12.0 | 24 | 28 | 12 | 1520.11 | 50 | |
| Pg 16 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1520.16 | 50 | |



Progress GFK

| 灰绿色RAL7009 两件套密封件 | | | | | | | Greygreen RAL 7009 Two-piece sealing insert | | | |
|----------------------|-----------------|-----------------|-----------------|-----------------|----|---------|--|----------------|----|--|
| G | > Ø < min mm | > Ø < max mm | > Ø < min mm | > Ø < max mm | mm | H mm | L mm | 型号 Art. No. | 📦 | |
| Pg 9 | 6.0 | 8.0 | 8.0 | 10.5 | 21 | 26 | 12 | 1570.09 | 50 | |
| Pg 11 | 5.5 | 8.5 | 8.5 | 12.0 | 24 | 28 | 12 | 1570.11 | 50 | |
| Pg 13 | 8.0 | 8.0 | 8.0 | 15.0 | 27 | 28 | 13 | 1570.13 | 50 | |
| Pg 16 | 8.0 | 11.0 | 11.0 | 15.0 | 27 | 28 | 13 | 1570.16 | 50 | |
| Pg 21 | 12.5 | 16.0 | 16.0 | 20.5 | 34 | 33 | 13 | 1570.21 | 25 | |
| Pg 29 | 19.0 | 23.0 | 23.0 | 27.5 | 41 | 36 | 13 | 1570.29 | 25 | |




1
2
3
4
5
6
7
8
9
10
11
12

Progress® GFK 尼龙电缆接头，适用于安装多根电缆

Synthetic cable glands Progress® GFK for installation of multiple cables

公制螺纹 | Entry thread metric



材质: 玻璃纤维增强聚酰胺
 性能: 无卤素
 密封件: TPE
 应力消除: 根据EN62444版本A
 温度范围: -20°C / +100°C
 防护等级: IP68

Material: Polyamide glass fiber reinforced
 Properties: halogen-free
 Seal: TPE
 Strain relief: Version A acc. to EN 62444
 Temperature range: -20°C / +100°C
 Protection class: IP 68



Progress GFK Multi

浅灰色RAL7035
 单体密封件

Light grey RAL 7035
 One-piece sealing insert



| G | > Ø < min mm | > Ø < max mm | ⊗ | ⊗ mm | H mm | L mm | 型号 Art. No. | 📦 |
|---------|-----------------|-----------------|---|---------|---------|---------|---------------|----|
| M16x1.5 | 2.0 | 3.0 | 2 | 21 | 26 | 12 | 1571.17.2.030 | 50 |
| M16x1.5 | 2.5 | 4.0 | 2 | 21 | 26 | 12 | 1571.17.2.040 | 50 |
| M16x1.5 | 3.5 | 5.0 | 2 | 21 | 26 | 12 | 1571.17.2.050 | 50 |
| M20x1.5 | 3.5 | 5.0 | 2 | 27 | 28 | 13 | 1571.20.2.050 | 50 |
| M20x1.5 | 4.5 | 6.0 | 2 | 27 | 28 | 13 | 1571.20.2.060 | 50 |
| M20x1.5 | 5.5 | 7.5 | 2 | 27 | 28 | 13 | 1571.20.2.075 | 50 |
| M20x1.5 | 3.5 | 5.0 | 3 | 27 | 28 | 13 | 1571.20.3.050 | 50 |
| M20x1.5 | 4.5 | 6.0 | 3 | 27 | 28 | 13 | 1571.20.3.060 | 50 |
| M20x1.5 | 5.2 | 6.5 | 3 | 27 | 28 | 13 | 1571.20.3.065 | 50 |
| M20x1.5 | 3.5 | 5.0 | 4 | 27 | 28 | 13 | 1571.20.4.050 | 50 |
| M20x1.5 | 4.5 | 6.0 | 4 | 27 | 28 | 13 | 1571.20.4.060 | 50 |
| M25x1.5 | 5.0 | 7.0 | 2 | 34 | 33 | 13 | 1571.25.2.070 | 25 |
| M25x1.5 | 6.7 | 9.0 | 2 | 34 | 33 | 13 | 1571.25.2.090 | 25 |
| M25x1.5 | 7.7 | 10.0 | 2 | 34 | 33 | 13 | 1571.25.2.100 | 25 |
| M25x1.5 | 5.5 | 7.0 | 3 | 34 | 33 | 13 | 1571.25.3.070 | 25 |
| M25x1.5 | 6.8 | 9.0 | 3 | 34 | 33 | 13 | 1571.25.3.090 | 25 |
| M25x1.5 | 5.5 | 7.0 | 4 | 34 | 33 | 13 | 1571.25.4.070 | 25 |
| M25x1.5 | 4.8 | 6.0 | 6 | 34 | 33 | 13 | 1571.25.6.060 | 25 |
| M32x1.5 | 9.0 | 11.5 | 2 | 41 | 35 | 15 | 1571.32.2.115 | 25 |
| M32x1.5 | 7.0 | 9.0 | 3 | 41 | 35 | 15 | 1571.32.3.090 | 25 |
| M32x1.5 | 8.5 | 10.5 | 3 | 41 | 35 | 15 | 1571.32.3.105 | 25 |
| M32x1.5 | 7.0 | 9.0 | 4 | 41 | 35 | 15 | 1571.32.4.090 | 25 |
| M32x1.5 | 5.8 | 7.0 | 6 | 41 | 35 | 15 | 1571.32.6.070 | 25 |

可根据要求提供其他型号和颜色，例如：
 深灰色RAL 7001，黑色RAL 9005，大螺纹


Additional versions and colours are available upon request:
 e.g. dark grey RAL 7001, black RAL 9005, larger entry threads

Progress® GFK 尼龙电缆接头，适用于安装多根电缆 Synthetic cable glands Progress® GFK for installation of multiple cables

Pg 螺纹 | Entry thread Pg

材质: 玻璃纤维增强聚酰胺
性能: 无卤素
密封件: TPE
温度范围: -20°C / +100°C
防护等级: IP68

Material: Polyamide glass fiber reinforced
Properties: halogen-free
Seal: TPE
Temperature range: -20°C / +100°C
Protection class: IP 68



Progress GFK Multi

| 浅灰色RAL7035 单体密封件 | | | | | | | Light grey RAL 7035 One-piece sealing insert | | |
|---------------------|---------------|---------------|---|----|---------|---------|---|----|--|
| G | >Ø< min mm | >Ø< max mm | | | H mm | L mm | 型号 Art. No. | | |
| Pg 9 | 2.0 | 3.0 | 2 | 21 | 26 | 12 | 1571.09.2.030 | 50 | |
| Pg 9 | 2.5 | 4.0 | 2 | 21 | 26 | 12 | 1571.09.2.040 | 50 | |
| Pg 9 | 3.5 | 5.0 | 2 | 21 | 26 | 12 | 1571.09.2.050 | 50 | |
| Pg 11 | 3.5 | 5.0 | 2 | 24 | 28 | 12 | 1571.11.2.050 | 50 | |
| Pg 11 | 4.5 | 6.0 | 2 | 24 | 28 | 12 | 1571.11.2.060 | 50 | |
| Pg 11 | 3.5 | 5.0 | 3 | 24 | 28 | 12 | 1571.11.3.050 | 50 | |
| Pg 13 | 3.5 | 5.0 | 2 | 27 | 28 | 13 | 1571.13.2.050 | 50 | |
| Pg 13 | 4.5 | 6.0 | 2 | 27 | 28 | 13 | 1571.13.2.060 | 50 | |
| Pg 13 | 5.5 | 7.5 | 2 | 27 | 28 | 13 | 1571.13.2.075 | 50 | |
| Pg 13 | 3.5 | 5.0 | 3 | 27 | 28 | 13 | 1571.13.3.050 | 50 | |
| Pg 13 | 4.5 | 6.0 | 3 | 27 | 28 | 13 | 1571.13.3.060 | 50 | |
| Pg 13 | 5.2 | 6.5 | 3 | 27 | 28 | 13 | 1571.13.3.065 | 50 | |
| Pg 13 | 3.5 | 5.0 | 4 | 27 | 28 | 13 | 1571.13.4.050 | 50 | |
| Pg 13 | 4.5 | 6.0 | 4 | 27 | 28 | 13 | 1571.13.4.060 | 50 | |
| Pg 16 | 3.5 | 5.0 | 2 | 27 | 28 | 13 | 1571.16.2.050 | 50 | |
| Pg 16 | 4.5 | 6.0 | 2 | 27 | 28 | 13 | 1571.16.2.060 | 50 | |
| Pg 16 | 5.5 | 7.5 | 2 | 27 | 28 | 13 | 1571.16.2.075 | 50 | |
| Pg 16 | 3.5 | 5.0 | 3 | 27 | 28 | 13 | 1571.16.3.050 | 50 | |
| Pg 16 | 4.5 | 6.0 | 3 | 27 | 28 | 13 | 1571.16.3.060 | 50 | |
| Pg 16 | 5.2 | 6.5 | 3 | 27 | 28 | 13 | 1571.16.3.065 | 50 | |
| Pg 16 | 3.5 | 5.0 | 4 | 27 | 28 | 13 | 1571.16.4.050 | 50 | |
| Pg 16 | 4.5 | 6.0 | 4 | 27 | 28 | 13 | 1571.16.4.060 | 50 | |
| Pg 21 | 5.0 | 7.0 | 2 | 34 | 33 | 13 | 1571.21.2.070 | 25 | |
| Pg 21 | 6.7 | 9.0 | 2 | 34 | 33 | 13 | 1571.21.2.090 | 25 | |
| Pg 21 | 7.7 | 10.0 | 2 | 34 | 33 | 13 | 1571.21.2.100 | 25 | |
| Pg 21 | 5.5 | 7.0 | 3 | 34 | 33 | 13 | 1571.21.3.070 | 25 | |
| Pg 21 | 6.8 | 9.0 | 3 | 34 | 33 | 13 | 1571.21.3.090 | 25 | |
| Pg 21 | 5.5 | 7.0 | 4 | 34 | 33 | 13 | 1571.21.4.070 | 25 | |
| Pg 21 | 4.8 | 6.0 | 6 | 34 | 33 | 13 | 1571.21.6.060 | 25 | |
| Pg 29 | 7.5 | 9.0 | 3 | 41 | 36 | 13 | 1571.29.3.090 | 25 | |

可根据要求提供其他型号和颜色，例如：
深灰色RAL 7001，黑色RAL 9005，大螺纹

Additional versions and colours are available upon request:
e.g. dark grey RAL 7001, black RAL 9005, larger entry threads

